

10-26-00

A

NEW APPLICATION TRANSMITTAL

ASSISTANT COMMISSIONER FOR PATENTS
Box Patent Application
Washington, D.C. 20231

PATENT

Attorney Docket No.: 19880-000610

Client Reference No.: 175

Dear Sir or Madam:

Transmitted herewith for filing under 37 CFR §1.53(b) is a non-provisional patent application of:

Applicant(s): DONALD F. GORDON
For: METHOD AND APPARATUS FOR PERFORMING DIGITAL-TO-DIGITAL VIDEO INSERTION

Enclosed are:

Patent Application - 10 pages of Specification, 4 pages of Claims, 1 page of Abstract, and 4 sheets of formal drawings

An unsigned Declaration

An unsigned Statement to establish Small Entity Status under 37 CFR §1.9 and §1.27


APPLICANT REQUESTS DEFERRAL OF THE FILING FEE UNTIL
THE RESPONSE TO THE NOTICE OF MISSING PARTS

PLEASE DO NOT CHARGE THE DEPOSIT ACCOUNT FOR THE FILING FEE

Please charge Deposit Account No 50-1229 as follows:

Any additional fees associated with this paper or during the pendency of this application.

Respectfully submitted,



Truong T. Dinh
Reg. No. 40,993

DINH & ASSOCIATES
2506 Ash Street
Palo Alto, California 94306
Tel: (650) 289-0600
Fax: (650) 289-0700

Express Mailing Label No.: EK377460960US

Date of Deposit: 10/24/00

I hereby certify that this correspondence is being deposited with the United States Postal Service "Express Mail Post Office to Addressee" service under 37 CFR § 1.10 on the date indicated above and addressed to: Assistant Commissioner for Patents, Washington, D.C. 20231

By: 
Truong T. Dinh

**VERIFIED STATEMENT (DECLARATION) CLAIMING SMALL ENTITY STATUS
(37 CFR 1.9(f) & 1.27(c)) - SMALL BUSINESS CONCERN**

Applicant or Patentee: **DONALD F. GORDON**
Title: **METHOD AND APPARATUS FOR PERFORMING DIGITAL-TO-DIGITAL
VIDEO INSERTION**
Application Serial No.: **Unassigned**
Filing Date: **10/24/00**

I hereby declare that I am:

- ☐ the owner of the small business concern identified below:
☐ an official of the small business concern empowered to act on behalf of the concern identified below:

Name of Small Business Concern: **DIVA Systems Corporation**
Address of Small Business Concern: **800 Saginaw Drive, Redwood City, CA, 94063**

I hereby declare that the above-identified small business concern qualifies as a small business concern as defined in 13 CFR §121.12, and reproduced in 37 CFR §1.9(d), for purposes of paying reduced fees to the United States Patent and Trademark Office, in that the number of employees of the concern, including those of its affiliates, does not exceed 500 persons. For purposes of this statement, (1) the number of employees of the business concern is the average over the previous fiscal year of the concern of the persons employed on a full-time, part-time or temporary basis during each of the pay periods of the fiscal year, and (2) concerns are affiliates of each other when either, directly or indirectly, one concern controls or has the power to control the other, or a third party or parties controls or has the power to control both.

I hereby declare that rights under contract or law have been conveyed to and remain with the small business concern identified above with regard to the invention, entitled **METHOD AND APPARATUS FOR PERFORMING DIGITAL-TO-DIGITAL VIDEO INSERTION** by inventor(s) **DONALD F. GORDON** described in Application Serial No. **Unassigned**, filed 10/24/00.

If the rights held by the above identified small business concern are not exclusive, each individual, concern or organization having rights in the invention is listed below* and no rights to the invention are held by any person, other than the inventor, who would not qualify as an independent inventor under 37 CFR §1.9(c) if that person made the invention, or by any concern that would not qualify as a small business concern under 37 CFR §1.9(d), or a nonprofit organization under 37 CFR §1.9(e).

*NOTE: Separate verified statements are required from each named person, concern or organization having rights to the invention averring to their status as small entities. (37 CFR §1.27)

Name: **DIVA Systems Corporation**
Address: **800 Saginaw Drive, Redwood City, CA, 94063**
☐ Individual ☐ Small Business Concern ☐ Nonprofit Organization

I acknowledge the duty to file, in this application or patent, notification of any change in status resulting in loss of entitlement to small entity status prior to paying, or at the time of paying, the earliest of the issue fee or any maintenance fee due after the date on which status as a small entity is no longer appropriate. (37 CFR §1.28(b)).

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under section 1001 of Title 18 of the United States Code, and that such willful false statements may jeopardize the validity of the application, any patent issuing thereon, or any patent to which this verified statement is directed.

Name of Person Signing: Stephanie Storms
Title of Person if other than Owner: Senior Vice President
Address of Person Signing: 800 Saginaw Drive, Redwood City, CA, 94063

Signature: _____ Date: _____

Attorney Docket No.: 19880-000610
Client Reference No.: 175

PATENT APPLICATION

METHOD AND APPARATUS FOR PERFORMING DIGITAL-TO-DIGITAL VIDEO INSERTION

Inventors:

Donald F. Gordon, a citizen of United States, residing at,
170 Formway Court
Los Altos, CA 94022

Assignee:

DIVA Systems Corporation
800 Saginaw Drive
Redwood City, CA 94063

Entity: Small business concern

DINH & ASSOCIATES
2506 Ash Street
Palo Alto, CA 94306
Tel (650) 289-0600
Fax (650) 289-0700

METHOD AND APPARATUS FOR PERFORMING DIGITAL-TO-DIGITAL VIDEO INSERTION

CROSS-REFERENCES TO RELATED APPLICATIONS

5 This application claims the benefit of U.S. provisional Application Serial No. 60/161,320, entitled "METHOD AND APPARATUS FOR PERFORMING DIGITAL-TO-DIGITAL VIDEO ADVERTISEMENT INSERTION," filed October 25, 1999, which is incorporated herein by reference in its entirety for all purposes.

BACKGROUND OF THE INVENTION

10 The invention relates generally to digital video processing and more specifically to a method and apparatus for inserting a compressed digital advertisement video into a compressed digital program video.

15 In modern television programming, it is desirable to seamlessly insert advertising information into a program video such that a viewer does not observe unsightly artifacts or other anomalies on a television screen when the program transitions into an advertisement or vice versa. The process by which advertisement is spliced into a program video is known as "ad insertion". Conventionally, ad insertion is typically achieved by merging an analog advertisement video into an analog program video (which is also known as a "digital-into-analog" process). This insertion technique works by switching between (advertisement and program) video sources and broadcasting the multiplexed video to the viewer. If the advertisement is stored in a digital format, it is typically converted into an analog advertisement video prior to the ad insertion. Frame synchronization is typically a major concern in such an analog-based system, and other issues are not quite as critical. 20 Since the video signal being broadcast is analog, the ad insertion equipment produces the multiplexed video in analog format regardless of whether the advertisement is stored in analog or digital format.

25 As television transmission systems switch to compressed digital formats, the need to insert advertisement using a "digital-into-digital" process becomes obvious. The digital-into-digital process achieves ad insertion by switching between compressed advertisement and program video streams and broadcasting the multiplexed output video stream to the viewer. Conventional solutions for the digital-into-digital process, however, are fraught with problems since video compression schemes such as the ones defined by the 30

Moving Pictures Expert Group (MPEG) standard focuses mainly on the relationships between frames of video and packets of audio.

Splicing in the compressed digital domain to achieve ad insertion generally cannot be accomplished with the same degree of freedom as in the analog domain or in the uncompressed digital domain. The profile (or characteristics, which typically include the bit rate) of a compressed video stream continually changes over time depending on the contents of the video, the parameter values used to encode the video, and other factors. Unless care is taken to ensure that the splicing is accomplished at the proper points within the compressed video stream and with matched encoding profiles for the compressed streams to be merged, various unsightly artifacts or other anomalies can result in the multiplexed output video. Such artifacts and anomalies may include, for example, severe macroblocking, dropped frames, macroblock panics, audio glitches, pop gargling noises, drop outs, and so on.

Therefore, digital-into-digital ad insertion techniques that seamlessly merge compressed digital advertisement video into compressed digital program video are highly desirable.

SUMMARY OF THE INVENTION

The invention provides ad insertion techniques that overcome disadvantages normally associated with conventional ad insertion techniques and can be used to seamlessly merge compressed digital advertisement video into compressed digital program video. The techniques of the invention utilize program video "profiling" to ensure that the digitally encoded advertisement video (i.e., compressed advertisement video) has a profile that is similar to that of the compressed digital program video at approximately the time the compressed advertisement video is inserted into the compressed program video. By using the techniques of the invention, the video decoder (e.g., in the subscriber equipment) can seamlessly decode both the program and advertisement without producing visible artifacts on the display during or after the transition from program to advertisement or advertisement to program.

The techniques of the invention can be advantageously applied in a digital information distribution system such as a video on demand system or a server-centric interactive program guide system. Such information distribution system may include service provider equipment, a data distribution network, and subscriber equipment that typically includes a video decoder and a display.

An embodiment of the invention provides an ad insertion processor (which typically resides in the service provider equipment) capable of seamlessly inserting a second compressed (e.g., advertisement) video stream into a first compressed (e.g., program) video stream. The ad insertion processor includes a real time encoder (e.g., an MPEG encoder), a
5 profiler, and a multiplexer, and typically further includes a buffer. To process a number of program and advertisement videos, the ad insertion processor is typically implemented with a number of real time encoders, buffers, profilers, and multiplexers.

The profiler receives the compressed program video stream and provides a profile for this stream. The profile is typically in the form of a continuous information
10 stream that includes bit rate information (e.g., a high and low bit rate value and a mean bit rate value) and may further include VBV (video buffering verifier) buffer information used for the compressed video stream. The profiling information for the compressed program video stream is used to facilitate the splicing of the compressed advertisement video stream into the compressed program video stream in a seamless manner.

15 An advertisement video source provides a number of advertisement videos. Upon receiving a control signal (e.g., a "pre-roll" signal that typically occurs six seconds before the advertisement is needed), the ad insertion source provides a selected advertisement video to the real time encoder.

20 The real time encoder receives and encodes the advertisement video in accordance with a particular encoding scheme to generate the compressed advertisement video stream. The real time encoder further controls the encoding of the advertisement video based at least in part on the profile of the compressed program video stream such that the profile of the compressed advertisement video stream approximately matches the profile of the compressed program video stream at the point in time the advertisement video is
25 inserted into the program video.

The buffer may be utilized to buffer the compressed advertisement until it is needed by the multiplexer (e.g., to buffer six seconds of video). The buffer can provide the compressed advertisement video to the multiplexer upon receiving another control signal (e.g., a "roll" signal).

30 The multiplexer receives the compressed advertisement and program video streams and inserts the compressed advertisement video stream into the compressed program video stream. This can be achieved by switching from the compressed program video stream to the compressed advertisement video stream, splicing the streams together, and providing the spliced stream as an output video stream. By using feedback of the profile of

the compressed program video to control the encoding of the advertisement video, when the multiplexer switches from the compressed program video to the compressed advertisement video, the switching appears seamless at a decoder.

The profiler further collects information regarding the profile of the compressed advertisement video such that the encoding parameters for the advertisement can be adjusted to ensure that the profile of the compressed advertisement video is similar to that of the compressed program video at the time the program video was interrupted to insert the advertisement video. In this manner, the transition back to the compressed program video from the compressed advertisement video will also be seamless.

The invention further provides other systems and methods that implement, process, and/or facilitate the ad insertion techniques described herein.

The foregoing, together with other aspects of this invention, will become more apparent when referring to the following specification, claims, and accompanying drawings.

BRIEF DESCRIPTION OF THE DRAWINGS

The teachings of the invention can be readily understood by considering the following detailed description in conjunction with the accompanying drawings.

FIG. 1 depicts a block diagram of a digital information distribution system capable of implementing various aspects of the invention;

FIG. 2 depicts a block diagram of an embodiment of an ad insertion processor in accordance with an embodiment of the invention;

FIG. 3 is a more detailed block diagram of an embodiment of a portion of the ad insertion processor of FIG. 2, which can be used to splice an advertisement video into a program video; and

FIG. 4 is a flow diagram of a video insertion process in accordance with an embodiment of the invention.

DESCRIPTION OF THE SPECIFIC EMBODIMENTS

FIG. 1 depicts a block diagram of a digital information distribution system 100 capable of implementing various aspects of the invention. System 100 includes service provider equipment 102, a data distribution network 104, and subscriber equipment 106. In an embodiment, service provider equipment 102 includes a digital program video source 108 (which may be implemented with a video server), a controller 110, an ad insertion processor

112, and a modulator 114 (which may be implemented as a quadrature amplitude modulation (QAM) modulator). Service provider equipment 102 couples to data distribution network 104, which may be a hybrid fiber-coax network. Subscriber equipment 106 also couples to network 104 and includes a video decoder 116 (e.g., an MPEG decoder) and a display device 118 (e.g., a television set).

Digital program video source 108 provides a number of streams of compressed digital program video to ad insertion processor 112. As used herein, the term "compressed digital program video" or "compressed video" includes the associated digital audio information, which may or may not be compressed. The compressed program video streams from source 108 may be MPEG-compliant streams. However, streams produced using other encoding schemes can also be processed in accordance with the techniques of the invention.

Ad insertion processor 112 generates a number of compressed advertisement video streams, inserts the compressed advertisement video streams into the compressed program video streams, and provides one or more output video streams to modulator 114. Modulator 114 then modulates the output video streams onto one or more carriers, and the modulated signals are transmitted via data distribution network 104 to subscriber equipment 106. Subscriber equipment 106 demodulates the signal, decodes a selected video stream using video decoder 116, and provides the decoded video to display 118.

Ad insertion processor 112 provides a seamless transition between the compressed program video that is distributed to the subscribers and the compressed advertisement video that is inserted into the compressed program video, and is described in further detail below. Controller 110 provides the control signals for the insertion of the compressed advertisement video into the compressed program video.

FIG. 2 depicts a block diagram of an embodiment of ad insertion processor 112. In this embodiment, ad insertion processor 112 includes an advertisement video source 200, a number of real time (one or more) encoders 202, a number (one or more) of buffers 204, and a processing unit 206. In an embodiment, processing unit 206 includes a profiler, a splicer, and a multiplexer.

Advertisement video source 200 provides the advertisements to be inserted into the program videos. Advertisement video source 200 may be implemented with a server coupled to a bulk storage device (e.g., a disk drive, magneto-optical drive, or some other storage device) used to store a large number of advertisements that can be selectively retrieved. The stored advertisements may be in a particular format and may conform to, for

example, the CCIR-601 video standard. Advertisement video source 200 receives from controller 110 control information identifying when an advertisement should be inserted into the compressed program video stream, and uses the control information to initiate the processing (e.g., encoding) of the advertisement. At the designated times, the selected
5 advertisements are streamed out of advertisement video source 200 to the assigned real time encoders 202 on a frame-by-frame or sub-frame (slice) basis.

Each real time encoder 202 may be assigned to encode a particular advertisement video from advertisement video source 200 or any number of encoders (e.g. two) can be used to encode the advertisement videos where each advertisement video time-
10 shares the available encoders. Real time encoders 202 then provide the compressed advertisement video streams to respective buffers 204, which buffer the compressed streams until they are needed.

Processing unit 206 receives a number of compressed program video streams (e.g., from program video source 108). For each compressed program video stream to be
15 inserted with advertisements, the profiler within processing unit 206 provides a profile for the compressed stream. Processing unit 206 further receives compressed advertisement video streams from buffers 204 and inserts the advertisements into the proper program videos.

FIG. 3 is a more detailed block diagram of an embodiment of a portion of ad
20 insertion processor 112, which is used to splice an advertisement video into a compressed program video stream. As shown in FIG. 3, the compressed program video is provided to a profiler 310 and a multiplexer 312 within processing unit 206.

Profiler 310 provides information regarding the profile of the compressed program video stream. This profile typically comprises information pertaining to various
25 parameters associated with the compressed stream such as, for example, bit rate information, VBV (video buffering verifier) buffer information that is typically used for MPEG encoding, intra DC coefficient precision, group of pictures (GOP) prediction format, and so on. The bit rate information may include, for example, a high bit rate value, a low bit rate value, and a mean bit rate value for the compressed stream. As used herein, the term “profile” includes
30 the context represented by “levels” in MPEG standard and it is not bound to the defined profile & level definitions and combinations used in MPEG standard. In general, a number of parameters are selected as representative of the program video stream encoding scheme and these parameters are continuously tracked by the profiler 310 for any instant parameter changes in the program bitstream. The profile information for the compressed program

video is provided (i.e., fed back) to a real time encoder 202x assigned to encode the advertisement video to be inserted into that program video.

As shown in FIG. 3, real time encoder 202x encodes the advertisement video in accordance with a particular encoding scheme to generate the compressed advertisement video stream. Real time encoder 202x may be implemented as an MPEG-2 encoder that generates an MPEG-compliant stream. Alternatively, real time encoder 202 may be designed to encode the advertisement video using some other encoding scheme. Typically, real time encoder 202x implements the same encoding scheme used to generate the compressed program video stream.

The encoding of the advertisement can begin a particular "pre-roll" time period (e.g., six seconds) prior to the time the advertisement is to be inserted into the compressed program video. The encoding start time can be indicated by a "pre-roll" signal that is received by controller 110 and which indicates that the advertisement will be needed in approximately that pre-roll time period (e.g., in six seconds). Controller 110 then notifies ad insertion processor 112 to produce the compressed advertisement video within that pre-roll time period. Thus, upon receiving the pre-roll signal, advertisement video source 200 can begin streaming frames or slices of the advertisement video to the assigned real time encoder 202x, which compresses the advertisement.

The encoding is typically initiated a short time (e.g., the pre-roll time) prior to the time at which the compressed video stream will be needed. This allows the real time encoder a sufficient amount of time to adjust the encoding parameters and then encode the advertising content.

The compressed advertisement video stream is then provided to an associated buffer 204x, which buffers the compressed advertisement video for that pre-roll time period (e.g., six seconds). If real time encoder 202x is capable of rapidly encoding video, buffer 204x may not be needed and, in that case, encoder 202x may be coupled directly to multiplexer 312 within processing unit 206.

In an implementation, a "roll" signal by controller 110 informs that the advertisement is to be inserted into the program video in a particular roll time period (e.g., one second). If buffer 204x is not employed, encoder 202x can begin encoding the advertisement video at this time and directly provide the compressed advertisement video stream to multiplexer 312.

At the specific point in time the compressed advertisement video is to be inserted into the compressed program video, multiplexer 312 switches from the compressed

program video stream to the compressed advertisement video stream. Splicer 314 then splices the compressed advertisement video stream to the compressed program video stream to generate a compressed output video stream.

Prior to the time the advertisement video is inserted into the compressed
5 program video stream, the profiling information that characterizes the compressed program video is provided (i.e., fed back) to real time encoder 202x used to encode the advertisement video for this program video. The profile is then used to adjust the encoder parameters to ensure that the profile of the compressed advertisement video approximately matches the profile of the compressed program video at the point when multiplexer 312 switches stream
10 and the compressed advertisement video is inserted into the compressed program video. Since the advertisement video has been compressed to ensure that the profile of the compressed advertisement video stream is similar to that of the compressed program video stream, the insertion of the advertisement into the program video appears seamless.

Various encoding parameters for the advertisement video can be adjusted
15 based on the profile of the compressed program video. For example, the quantization step size used in the encoding process can be adjusted to achieve the desired profile. The quantization step size can be decreased if a higher bit rate is needed and can be increased if a lower bit rate is required. The VBV buffer information can also be used in the encoding process to ensure that the multiplexed output video stream will not cause buffer overflow or
20 underflow at the decoder. These adjustments of the encoding process are known in the art and not described in further detail herein.

The contents of the program video may be very different from that of the advertisement video and this may result in a difference in picture quality (as measured by the signal-to-noise ratio) for the same profile. In an embodiment, for a particular period of time
25 (e.g., several seconds) near a splicing point, the quality of the advertisement video can be matched to that of the program video. This matching of the picture quality of the two videos to be spliced can be achieved by adjusting the profile parameters.

In an embodiment, while the compressed advertisement video is streamed to multiplexer 312 (after the advertisement video has been spliced to the program video
30 stream), profiler 310 collects profile parameter information according to which the encoding parameters are adjusted. Profile parameters such as the instantaneous bit rate of the advertising video stream are adjusted so that the profile parameter values closely matches program video parameters at the time the program video was interrupted. This is particularly important at the time the advertising video ends and is transitioned back to program video.

The use of the profile to continuously adjust the encoding parameters of the advertisement video ensures that the splicing of the program video back into the advertisement appears seamless.

5 A number of advertisements may be inserted sequentially into the program video using the techniques described above. In an embodiment, the advertisements may be encoded one after another using a number of real time encoders 202 that may be arranged in a cascade configuration. Each advertisement may be encoded based on the profile obtained for the program video into which the advertisement is to be inserted. Multiplexer 312 can switch from one encoded advertisement video stream to another until all advertisements
10 have been inserted. At the end of the advertisements, multiplexer 312 switches back to the compressed program video stream. The profile of the compressed program video is used to adjust the encoder parameters for the advertisements and to ensure that the last advertisement to be encoded has a profile that approximately matches the profile of the compressed program video at the point in time the program video was paused to insert the
15 first advertisement. In this manner, the advertisement videos can be seamlessly inserted into the program video. In addition to the last advertisement video, the first advertisement video may also be encoded with the same profile as the compressed program video to provide seamless transition.

20 In an alternative embodiment, the advertisements may be encoded one after another using only one real time encoder 202. Again, the encoding of each advertisement can be controlled based on the profile of the compressed program video to ensure a seamless transition between the advertisements and the program video.

25 Because the profile of the compressed program video stream was used to encode the advertisements inserted into the program video, the decoder within the subscriber equipment is able to properly decode the multiplexed output video stream without producing artifacts and anomalies on the video display. Since the profile of the inserted advertisement is similar to that of the program video, the decoding parameters and the decoder buffer are well behaved (e.g., no buffer overflow). Thus, the decoder can seamlessly transition from decoding the compressed program video stream to decoding the compressed advertisement
30 video stream.

In the above description, the program video is received in compressed form and the advertisement video is encoded based on the profile of the compressed program video. In other embodiments, the program video can also be received in uncompressed

form. In this case, the program video can be encoded in the normal manner and the profile for the advertising video can be generated as described above.

For clarity, various aspects of the invention are described for insertion of advertisement video into program video. The techniques described herein can also be adapted for encoding and inserting (i.e., splicing) any types of video or other source materials (e.g., audio, and so on). Moreover, the techniques described herein can be used to splice together compressed streams for portions of frames of videos (e.g., to splice a first compressed stream for the upper half of the frame with a second compressed stream for the lower half of the frame).

FIG. 4 is a flow diagram of a video insertion process 400 in accordance with an embodiment of the invention. Video insertion process 400 can be used to insert a second compressed video stream (e.g., for an advertisement) into a first compressed video stream (for a program video). Initially, the first compressed video stream is received, at step 412, and a profile for the stream is determined, at step 414. The profile can include the information described above.

A second video is then received, at step 416, and encoded in accordance with a particular encoding scheme and further based on the profile of the first compressed video stream to generate the second compressed video stream, at step 418. The encoding of the second video is controlled continuously based at least in part on the profile of the first compressed video stream, at step 420. The encoding can be initiated prior to the time the second compressed video stream is needed, and the encoding can be adjusted such that the profiles for the first and second compressed video streams approximately match. If the profiles for the streams do not match (within the requisite degree), the encoding parameters are further adjusted back at step 420. Otherwise, if the profiles approximately match, the second compressed video stream can be spliced and multiplexed into the first compressed video stream, at step 426.

The foregoing description of the preferred embodiments is provided to enable any person skilled in the art to make or use the invention. Various modifications to these embodiments will be readily apparent to those skilled in the art, and the generic principles defined herein may be applied to other embodiments without the use of the inventive faculty. Thus, the invention is not intended to be limited to the embodiments shown herein but is to be accorded the widest scope consistent with the principles and novel features disclosed herein.

WHAT IS CLAIMED IS:

1 1. A method for inserting a second compressed video stream into a first
2 compressed video stream, the method comprising:
3 receiving the first compressed video stream;
4 determining a profile for the first compressed video stream;
5 encoding a second video in accordance with a particular encoding scheme
6 and further with a profile similar to the profile of the first compressed video stream to
7 generate the second compressed video stream;
8 controlling the encoding of the second video based at least in part on the
9 profile of the first compressed video stream; and
10 inserting the second compressed video stream into the first compressed
11 video stream.

1 2. The method of claim 1, further comprising:
2 determining the profile for the second compressed video stream.

1 3. The method of claim 1, wherein the encoding of the second video is
2 controlled such that a profile for the second compressed video stream is similar to the
3 profile for the first compressed video stream at approximately a point in time when the
4 second compressed video stream is inserted into the first compressed video stream.

1 4. The method of claim 3, wherein the encoding of the second video is
2 further controlled such that the profile for the second compressed video stream is similar
3 to the profile for the first compressed video stream at approximately a point in time when
4 the first compressed video stream is inserted back into the second compressed video
5 stream.

1 5. The method of claim 1, wherein the inserting includes
2 initially multiplexing the first compressed video stream as an output video
3 stream;
4 multiplexing the second compressed video stream as the output video
5 stream at a point in time when the inserting is to be achieved; and

6 splicing the second compressed video stream to the first compressed video
7 stream.

1 6. The method of claim 5, further comprising:
2 pausing the first compressed video stream for the time during which the
3 second compressed video stream is multiplexed as the output video stream.

1 7. The method of claim 1, further comprising:
2 receiving a second control signal indicative of a second time period within
3 which the inserting is to be performed; and
4 initiating the encoding of the second video in response to receiving the
5 second control signal.

1 8. The method of claim 7, further comprising:
2 buffering the second compressed video stream prior to the inserting.

1 9. The method of claim 1, wherein the second video relates to an
2 advertisement and the first compressed video stream relates to a program video.

1 10. The method of claim 1, wherein the profile for the first compressed
2 video stream includes bit rate information related to the first compressed video stream.

1 11. The method of claim 10, wherein the bit rate information includes a
2 high bit rate, a low bit rate, and a mean bit rate determined over a particular time period.

1 12. The method of claim 10, wherein the profile for the first compressed
2 video stream further includes video buffering verifier (V BV) buffer information used for
3 the encoding.

1 13. The method of claim 1, wherein the second video is encoded in
2 accordance with an MPEG encoding scheme.

1 14. A system operative to insert a second compressed video stream into a
2 first compressed video stream, comprising:

3 a profiler configured to receive the first compressed video stream and
4 provide a profile for the first compressed video stream;
5 a real time encoder coupled to the profiler and configured to receive and
6 encode a second video in accordance with a particular encoding scheme and further with
7 a profile similar to the profile of the first compressed video stream to generate the second
8 compressed video stream, and wherein the real time encoder is further configured to
9 control the encoding of the second video based at least in part on the profile of the first
10 compressed video stream; and
11 a multiplexer operatively coupled to the real time encoder and operative to
12 receive the second and first compressed video streams and to insert the second
13 compressed video stream into the first compressed video stream.

1 15. The system of claim 14, further comprising:
2 a buffer coupled to the real time encoder and the multiplexer and
3 configured to receive and buffer the first compressed video stream from the real time
4 encoder.

1 16. The system of claim 14, wherein the multiplexer is further configured
2 to splice the second compressed video stream into the first compressed video stream.

1 17. The system of claim 14, wherein the profiler is further configured to
2 receive the second compressed video stream and provide a profile for the second
3 compressed video stream.

1 18. The system of claim 14, wherein the profile for the second
2 compressed video stream includes bit rate information related to the second compressed
3 video stream.

1 19. The system of claim 14, wherein the real time encoder is further
2 configured to control the encoding of the second video such that a profile for the second
3 compressed video stream is similar to the profile for the first compressed video stream at
4 approximately a point in time when the second compressed video stream is inserted into
5 the first compressed video stream.

1 20. The system of claim 19, wherein the real time encoder is further
2 configured to control the encoding of the second video such that the profile for the second
3 compressed video stream is similar to the profile for the first compressed video stream at
4 approximately a point in time when the first compressed video stream is inserted back
5 into the second compressed video stream.

**METHOD AND APPARATUS FOR PERFORMING
DIGITAL-TO-DIGITAL VIDEO INSERTION**

ABSTRACT OF THE DISCLOSURE

5

10

15

Techniques for seamlessly inserting a second compressed video stream (e.g., for an advertisement) into a first compressed video stream (e.g., for a program video), which can be implemented in an ad insertion processor that typically includes a real time encoder (e.g., an MPEG encoder), a buffer, a profiler, a multiplexer, and a splicer. The profiler receives the first compressed video stream and provides a "profile" for the stream, which may include bit rate and other information about the stream. The real time encoder receives and encodes a second video in accordance with a particular encoding scheme to generate the second compressed video stream. The real time encoder further controls the encoding of the second video based at least in part on the profile of the first compressed video stream such that the profiles for the two streams are approximately similar at the point in time the second stream is inserted into the first stream. The buffer stores the first compressed video stream from the real time encoder until it is needed. The multiplexer inserts the second compressed video stream into the first compressed video stream, and the splicer splices the two streams together to form the output video stream.




FIG. 1




FIG. 2





FIG. 3

**FIG. 4**

DECLARATION

As a below named inventor, I declare that:

My residence, post office address and citizenship are as stated below next to my name; I believe I am an original, first and sole inventor of the subject matter which is claimed and for which a patent is sought on the invention entitled: **METHOD AND APPARATUS FOR PERFORMING DIGITAL-TO-DIGITAL VIDEO INSERTION** the specification of which was filed on **10/24/00** as Application Serial No. **Unassigned**.

I have reviewed and understand the contents of the above-identified specification, including the claims, as amended by any amendment referred to above. I acknowledge the duty to disclose information that is material to patentability as defined in Title 37, Code of Federal Regulations, Section 1.56.

I claim no foreign priority benefits under Title 35, United States Code, Section 119.

I claim the benefit under Title 35, United States Code, Section 119(e) of any United States provisional application(s) listed below.

Application No.	Date of Filing
60/161,320	October 25, 2000

I further declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code, and that such willful false statements may jeopardize the validity of the application or any patent issuing thereon.

Full Name of Inventor 1	Last Name: GORDON	First Name: DONALD	Middle Name or Initial: F.	
Residence & Citizenship:	City: Los Altos	State/Foreign Country: CA	Country of Citizenship: US	
Post Office Address:	Post Office Address: 170 Formway Court	City: Los Altos	State/Country: CA	Postal Code: 94022
Signature & Date:	Signature of Inventor :		Date:	